

The building stock as an urban mine: estimation of the stock of recoverable materials in the regeneration of the built environment

A. Luciano, M. Cellurale, L. Cutaia, | Resources Valorization Laboratory, ENEA (IT)
S. Baiani, P. Altamura | Planning Design Technology of Architecture Department, «Sapienza»
University of Rome (IT)


9th International Conference on Sustainable Solid Waste Management
Corfu | 17.06.2022



1101 0110 1100
0101 0010 1101
0001 0110 1110
1101 0010 1101
1111 1010 0000



Construction chain and impacts



- ✓ Land and resources depletion:
 - 50% of all extracted materials (almost 2.6 billion tons in Europe and almost 150 million tons in Italy)
 - 50% of energy consumption
 - 30% of water consumption
- ✓ Huge amount of wastes
 - 30% of all produced wastes in Europe



High potential for the improvement of resource efficiency and the transition towards the circular economy

EU policies and strategies for resource efficiency and circularity in the construction sector

Waste hierarchy



EU Waste Framework Directive 98/2008

(Art. 11). 'by 2020, the preparing for re-use, recycling and other material recovery, ..., of non-hazardous construction and demolition wasteshall be increased to a **minimum of 70% by weight**'

Construction 2020 strategy | 2012

To be updated in 2021, it aimed at:


- stimulating favorable conditions for investments
- improving the human capital base in the construction sector
- improving **resource efficiency, environmental performance** and business opportunities
- strengthen the internal construction market
- promoting the global competitiveness of EU construction companies.

Resource Efficiency Opportunities in the Building Sector | 2014


Defines the steps towards a **better functioning market for recycled construction materials**.

EU Construction and Demolition Waste Protocol | 2016

Aims at increasing confidence in the C&D waste management process and in the quality of relative recycled materials.



EU policies and strategies for resource efficiency and circularity in the construction sector



The European Green Deal | COM/2019/640 final

- States the **important role of the construction sector** within the Green Deal
- Calls for a **renovation wave** for the building sector in 2020
- Foresees a **revision of the construction products regulation** promoting a **design of new and renovated buildings oriented towards the circular use of resources**
- Strictly **links several policies** falling under the umbrella of the EU Green Deal **with the construction sector** and its closely interconnected sectors, such as the mining quarrying and the **waste management**.

A new Circular Economy Action Plan For a cleaner and more competitive Europe | COM/2020/98 final

The EU Commission has committed to **launch a comprehensive Strategy for a Sustainable Built Environment in 2021**

The Action Plan **foresees to strengthen the circular use of materials** through:

- the improvement of the **durability** and **adaptability** of the built assets
- the integration of **life cycle assessment (LCA)** into public procurements
- the **revision of material recovery targets** with a focus on **insulation materials**
- the safe and circular use of excavated soil to reduce soil sealing.



Toward a resource Efficiency Plan

The potential in term of raw material substitution with by-products and recycled wastes is not adequately exploited


opportunities offered by the circular economy in the construction sector in terms of **waste valorisation and reuse**



Waste production, management

Resources Flow Analysis

Raw materials substitution




Luciano A., Cutaia L., Carletti R., Pentassuglia R., Elmo G., Mancini G.

Resources Optimization and sustainable waste management in construction chain in Italy: toward a resource efficiency plan. Waste and Biomass Valorization (2020) 11:5405–5417 <https://doi.org/10.1007/s12649-018-0533-1>

Urban mining and Regeneration closing the loops: an integrated management approach

Rethinking at the build environment as an urban mine and then to quantify the built environment stocks and to plan an exploitation of these resources



- Due to technical and socio-economic factors, the stock of materials in the built environment currently only marginally re-enter a closed loop of use
- For the purpose of recirculating the materials, it is necessary to define **which types** of materials are available, their **quantity**, **where** and **when they will be available**, **how** and **where they can be reused/recycled**, **how much it costs**.

ES-PA Project - "Energy and Sustainability for public administration" | Circular economy related research task



ENERGIA E SOSTENIBILITÀ
PER LA
PUBBLICA AMMINISTRAZIONE

_duration: 2017-2023
_budget: 9,6 M€



UNIONE EUROPEA
Fondo Sociale Europeo
Fondo Europeo di Sviluppo Regionale



Framework of actions to enhance the skills of the PA in the fields of energetic and ecological transitions

Task A2.3.2



Estimation of the materials that can be recovered in "urban mines" with a specific focus on the build environment

- **Expected output:** guidelines for businesses and public administrations aimed at estimating the quantities and characteristics of materials that can be used and recovered in urban and industrial areas (urban mining)
- **Recipients:** national and regional decision makers, officials and technicians
- **Implementation:** cognitive and **operational tools** will be **outlined for the estimation of residues and stocks present in urban and industrial areas, at different scales (macro/national, intermediate/regional/provincial, local/urban/district/building)** - for the implementation of plans and strategies for the recovery of building stocks.
- **Collaboration:** Research activity developed by Enea in collaboration with «Sapienza» University of Rome, with **circular design experiments on 3 case studies** in the city of **Rome** (IT), within urban regeneration/re-unctionalisation/renovation projects of existing buildings

ES-PA Project – Estimation of the stock of recoverable materials in the built environment and cycle closure: a multi scale toolkit




Multi-scale toolkit

- Identify the materials present in buildings (buildings stocks) in terms of type and quantity.
- define the flows deriving from different intervention scenarios on the buildings (traditional demolition, selective demolition, soft and deep renovation)
- identify the reuse/recovery rate of these materials in different intervention scenarios and available recovery technologies (e.g. valorisation and recovery plants)
- identify the options for reuse and recycling of these materials according to the urban planning (circular design)



ES-PA Project – Estimation of the stock of recoverable materials in the built environment: approaches and methodologies

- An increasing number of studies today are analysing – with different approaches - the stock of materials in the urban built environment intending to anticipate and stimulate its circular use and valorisation



ES-PA Project - "Task: Estimation of the stock of recoverable materials in the built environment"



Methodology:
bottom up +
top-down
approach =
multi-scale toolkit
for different types of
public
administrations to
help estimating and
planning the use of
secondary materials

Top-down approach based on **statistic data** to the analysis of the national building stock, considering the main building typologies

STEP 1 - Estimation of the national building stock for the main typologies (residential buildings, schools, industrial buildings)

STEP 2 - Definition of the constructive characteristics of exemplary buildings with commonly found materials and components

STEP 3 - Estimation of the material stock, aimed at the quantitative and qualitative evaluation of the main materials' availability

Bottom-up/experimental approach on the estimation of materials stock in specific **case studies** and of the potential flows and level of reusability/recyclability in different intervention scenarios

Phase 1: technological analysis of the building
Phase 2: identification and quantitative estimation of the materials stock in the buildings

Phase 3: architectural and environmental redevelopment project of the building with the adoption of circular strategies

Phase 4: quantitative estimation of the materials removed and identification of their final destination


Definition of a **toolkit** for **public administrations (local/regional/national)** to allow a quick estimate of materials stock based on different scenarios of transformation of the building stock

TOOL 1 (macro level) for the estimation of building stock at national level

TOOL 2 (meso level) for the estimation of building stock at regional level or at level of buildings type)

TOOL 3 (micro-level) for the estimation of building stock at municipal level/district level/

Case study 1: Urban regeneration and refurbishment of the public housing district of Torrevecchia, Rome (IT)



- Urban regeneration and environmental retrofit project of the public housing district of Torrevecchia in Rome (1.074 housing units for 3.600 inhabitants)
- *Construction period:* 1978-84
- *Construction system:* pre-fabricated reinforced concrete (coffrage-tunnel)
- *Other prevailing materials:* brick, gypsum board, iron (windows and parapets)

- The district contains recurring building types largely widespread in Italy with the same construction type and same materials




Research activity developed in collaboration with Sara Lucci, student of the Master Degree Course "Architecture-Urban Regeneration", "Sapienza" University of Rome (IT)

DEVELOPMENT STAGE



Phase 1

Technological analysis of the building



Phase 2

identification and quantitative estimation of stock materials



Phase 3

architectural and environmental redevelopment project of the building with the adoption of circular strategies



Phase 4

quantitative estimate of the materials removed and identification of the final destination

Case study 1: Urban regeneration and refurbishment of the public housing district of **Torrevecchia, Rome (IT)**


Phase 2 - inventory of the materials stock, making use of 3 indicators: volume, weight and embodied carbon
The stock analysis has identified reinforced concrete as the prevailing material in weight

Phase 3-4 - estimation of the amount and typologies of materials destined to be demolished in a renovation scenario, with solutions for their full recovery (18,5% on-site reuse, 60,3% off-site recycling, 21,1% remanufacturing).


Demolitions and estimate of volume/weight/embodied CO2 in existing materials




Circular design strategies




► Peso dei materiali principali allo stato di fatto





► CO2 incorporata nei materiali principali



► Gestione fine vita dei materiali da demolire



Case study 2: Re-functionalisation of the former public transport buses garage in Ragusa Square, Rome (IT)



Research activity developed in collaboration with Martina Avena, student of the Master Degree Course "Architecture-Urban Regeneration", "Sapienza" University of Rome (IT)


- Urban regeneration and re-functionalisation project of the disused ATAC (public transport buses) garage area in Piazza Ragusa in Rome (11.000 sqm)
- *Construction period*: 1928-1940 / 1953-1955
- *Construction system*: frame structure in reinforced concrete with thin vaulted roof
- *Other prevailing materials*: iron, bricks, plaster, wood, glass

DEVELOPMENT STAGE






Case study 2: Re-functionalisation of the former public transport buses garage in Ragusa Square, Rome (IT)


Weight:



Embodied carbon:




Case study 3: Renovation of the «ITIS Alessandro Volta» school building in Bravetta street, Rome (IT)



Research activity developed in collaboration with Gaetana Katia Bruno, student of the Master Degree Course "Architecture-Urban Regeneration", "Sapienza" University of Rome (IT)

- Urban regeneration and renovation project of the Industrial Technical Institute "Alessandro Volta" in Bravetta 351 street, Rome (IT)
- *Construction period*: 1963-1964, 1971-1972, 1982
- *Construction system*: suspended steel structure
- *Other prevailing materials*: concrete, fiber cement, glass

DEVELOPMENT STAGE



Case study 3: Renovation of the «ITIS Alessandro Volta» school building in Bravetta street, Rome (IT)

Criticalities in the materials stock, typical of the school buildings of the same age, that need to be solved to improve the level of recyclability

Presence of asbestos


- 1 In the fiber cement **PERIMETER FLAPS**
- 2 In the vinyl-asbestos used as a finish for the laboratories and/or classrooms **FLOORING** of 2 floors of the building
- 3 In the **TOP COVER** but in a good state of conservation both internally and externally

Carbonation of concrete

- 1 In the **PERIMETER BUFFERS** (breakdown of the masonry and oxidation of the reinforcement concrete covers exposed to the action of atmospheric agents)

Water infiltration and humidity

- 1 In the **FLOORS** (in predalles and covered with riverclack slabs)
- 2 In the suspended ceiling **PANELS**



Conclusions

- The combined top down and bottom up approach allows you to operate at different scales in order to give different solutions for different recipients (national governments for the development of national plans and strategy, local authorities for sectorial and urban planning)
- The results of the bottom up approaches activity provide useful inputs for the standardization of main building typologies in terms of recoverable stocks and reuse/recycling options

Antonella Luciano
antonella.luciano@enea.it



1101 0110 1100
0101 0010 1101
0001 0110 1110
1101 0010 1101
1111 1010 0000

